

SIZE AND SEATING CAPACITY CONFERENCE ROOM LAYOUT

CONFERENCE TABLE SIZE	SEATING CAPACITY	SUGGESTED ROOM SIZE	MINIMUM ROOM SIZE
72"(6')LX48"W	4-6	15'-4"X13'-4"	14'-0"X12'-0"
84"(7')LX48"W	4-6	16'-4"X13'-4"	15'-0"X12'-0"
96"(8')LX48"W	6-8	17'-4"X13'-4"	16'-0"X12'-0"
120"(10')LX48"W	8-10	19'-4"X13'-4"	18'-0"X12'-0"
144"(12')LX48"W	10-12	21'-4"X13'-4"	20'-0"X12'-0"
168"(14')LX48"W	12-14	23'-4"X13'-4"	22'-0"X12'-0"
192"(16')LX58"W	14-16	25'-4"X14'-2"	24'-0"X12'-10"
240"(20')LX58"W	18-20	29'-4"X14'-2"	28'-0"X12'-10"
288"(24')LX58"W	22-24	33'-4"X14'-2"	32'-0"X12'-10"

SEATING CAPACITY: CHART SUGGESTS A RANGE FROM COMFORTABLE SEATING TO FULL SEATING.
 SUGGESTED ROOM SIZE: ALLOWS 56" TO WALK BETWEEN WALL AND CHAIR BACK, 32" TO RISE FROM TABLE, AND 24" TO WALK.
 MINIMUM ROOM SIZE: ALLOWS MINIMUM OF 48" TO WALK SIDEWAYS BETWEEN WALL AND CHAIR BACK, 32" TO RISE FROM TABLE, AND 16" TO PASS.

DISCLAIMER: THESE GUIDELINES ARE OFFERED FOR GENERAL REFERENCE PURPOSES ONLY; EACH SPACE PLANNING PROJECT IS DIFFERENT AND SHOULD BE MANAGED WITH THE GUIDANCE OF AN EXPERIENCED PROFESSIONAL.

GUIDELINES

- ALLOW 48" BETWEEN TABLE AND WALL FOR MINIMUM CLEARANCES
- ALLOW 56" BETWEEN TABLE AND WALL FOR MORE COMFORTABLE SPACE
- ALLOW 16" TO WALK SIDEWAYS BETWEEN CHAIR AND WALL
- ALLOW 24" TO WALK BETWEEN CHAIR AND WALL WITHOUT TURNING SIDEWAYS
- ALLOW 30" SIDE TO SIDE PER CHAIR
- ALLOW 32" TO 34" BETWEEN TABLE AND BACK OF CHAIR TO RISE FROM CHAIR
- ALLOW 38" TO 40" BETWEEN TABLE AND BACK OF CHAIR TO RISE FROM CHAIR WHEN CONFINED BY OTHER SITTERS
- ALLOW 56" BETWEEN TABLE AND VISUAL DISPLAY BOARD
- ALLOW 36" BENDING SPACE TO USE UNDER COUNTER CABINETS OR LOWER SHELVES OF BOOKCASE
- ALLOW 72" BETWEEN TABLE AND WALL FOR 24"-DEEP STORAGE TOWERS AND CRENZAS
- ALLOW 30" BETWEEN TABLE AND BACK OF CHAIR TO USE KEYBOARD
- ALLOW 24" TO 30" FOR STANDING AND PRESENTING MATERIAL ON WALL
- TV OR MONITOR VIEWING RECOMMENDED AT 30 TO 45 DEGREES FROM CENTER OF THE SCREEN.

